

APPENDIX B (CALIBRATION TABLE)

Manufacturer	Series	Models	Inlet Diameter		Calibration Factor		cc / tip	Tips per test volume				
								150 cc	450 cc	750 cc	946 cc	
NovaLynx	2500	260-2500, 260-2500D, 260-2500E	8	inch	0.01	inch/tip	8.24	18.2	54.6	91.1	114.8	
	2500M	260-2500M, 260-2500ME		8	inch	1	mm/tip	32.43	4.6	13.9	23.1	29.2
		260-2500M.2, 260-2500ME.2		8	inch	0.2	mm/tip	6.49	23.1	69.4	115.6	145.9
		260-2500M.25, 260-2500ME.25		8	inch	0.25	mm/tip	8.11	18.5	55.5	92.5	116.7
		260-2500M.5, 260-2500ME.5		8	inch	0.5	mm/tip	16.21	9.3	27.8	46.3	58.3
	2500-12	260-2500-12, 260-2500E-12		12	inch	0.01	inch/tip	18.53	8.1	24.3	40.5	51.0
	2500M-12	260-2500M-12.2, 260-2500ME-12.2		12	inch	0.2	mm/tip	14.59	10.3	30.8	51.4	64.8
		260-2500M-12.25, 260-2500ME-12.25		12	inch	0.25	mm/tip	18.24	8.2	24.7	41.1	51.9
		260-2500M-12.5, 260-2500ME-12.5		12	inch	0.5	mm/tip	36.48	4.1	12.3	20.6	25.9
	2501	260-2501-A		8	inch	0.01	inch/tip	8.24	18.2	54.6	91.1	114.8
	2501M	260-2501M-A		8	inch	1	mm/tip	32.43	4.6	13.9	23.1	29.2
		260-2501M-A.2		8	inch	0.2	mm/tip	6.49	23.1	69.4	115.6	145.9
		260-2501M-A.25		8	inch	0.25	mm/tip	8.11	18.5	55.5	92.5	116.7
2505	260-2505		7.874	inch	0.01	inch/tip	7.98	18.8	56.4	94.0	118.6	
RM Young	52202	260-52202, 260-52202H, 260-52203		6.3	inch	0.1	mm/tip	2.01	75	224	373	470
Davis	7852	260-7852		6.502	inch	0.01	inch/tip	5.44	28	83	138	174
		260-7852M		6.502	inch	0.2	mm/tip	4.28	35	105	175	221
	6463	260-6463, 110-WS-16RC		6.5	inch	0.01	inch/tip	5.44	28	83	138	174
Qualimetrics	6011	260-6011-A, 260-6021-A, 260-6011-C		8.214	inch	0.01	inch/tip	8.68	17	52	86	109
		260-6011-B, 260-6021-B, 260-6011-D		8.214	inch	0.1	mm/tip	3.42	44	132	219	277
Campbell	TE525	260-TE525		6.06	inch	0.01	inch/tip	4.73	32	95	159	200
		260-TE525WS		8	inch	0.01	inch/tip	8.24	18	55	91	115
		260-TE525MM		9.66	inch	0.1	mm/tip	4.73	32	95	159	200
Rainwise	260-0111	260-0111-A, 110-WS-25RG, 260-WS-32RG		8	inch	0.01	inch/tip	8.24	18	55	91	115
Gill	MetPak RG	ARG 100		10	inch	0.2	mm/tip	10.13	15	44	74	93
			Length	Width								
La Crosse	TX10U	110-WS-18RG, 110-WS-25RG-P		4.94	2.156	0.02	inch/tip	3.49	43	129	215	271