

190-5xx Tripods

NovaLynx **190-5xx** tripods are sturdy and economical and may be used for temporary or permanent installations. These tripods may be ground-mounted or secured to the top of a building. Each tripod accommodates masts up to 1.75" (44.5mm) in diameter.

Masts of various lengths are available to reach the desired height. For tall installations, guy wire kits are available to ensure the tripod is stable even in windy conditions. NovaLynx offers lightning rods and earth-grounding kits for lightning protection.



190-505 Tripod (3')



190-510 Tripod (5')



190-520 Tripod (10')

Features

- Plated steel construction
- Folds for transport and storage
- Upper and lower mast clamps
- Accepts masts up to Ø 1.75" (Ø 44.5mm)
- Feet swivel for mounting on sloped roofs
- May be tipped down (one direction only)

	3' Tripod	5' Tripod	10' Tripod
Model	190-505	190-510	190-520
Height unfolded	32"	55"	120"
Width unfolded	32"	48"	32"
Weight (approx)	7.75 lbs (3.5 kg)	11.75 lbs (5.3 kg)	27 lbs (12.2)
Max mast diameter		1.75" (44 mm)	
Leg diameter		1.25" (32 mm)	

Ordering Information

190-505	3' Tripod	Mast diameter:	Ø1.25" (32 mm)
190-510	5' Tripod	Swaged one end:	Ø1.07" x 3.75" (Ø27 x 95mm)
190-510	10' Tripod		
190-302	3' Aluminum mast, swaged	190-318	8' Aluminum mast, swaged
190-312	5' Aluminum mast, swaged	190-322	10' Aluminum mast, swaged